

SPIDER

SPORTY LOOK

The only model available in the red flash SPIDER provides protection for outdoor activities.



SPIPSI



SPIESP



SPIFLASH



26 g

SUPPLIED WITH

Microfibre pouch
ETUIFS












- + NON-SLIP BRIDGE
- + LOWER PROTECTION
- + NON-SLIP TIPGRIP TEMPLES

bolle
SAFETY

SPIDER

SPORTY LOOK

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SPIDER	 Clear	SPIPSI	2C-1,2  1 FT KN CE	 EN166 FT CE	Anti-scratch(K)/anti-fog(N)
	 ESP	SPIESP	5-1,4  1 FT K CE	 EN166 FT CE	Anti-scratch(K)/anti-fog
	 Red flash	SPIFLASH	5-3,1  1 FT K CE	 EN166 FT CE	Anti-scratch(K)/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol,
authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

CE European standard  Manufacturer name

TECHNOLOGY

B-ESP

ESP, Extra Sensory Perception.

An innovative coating to reduce dazzle
and the harmful affects of blue light.


B-ESP filters 57% of blue light, transmits
64% of visible light, 99.99% of UVA/UVB.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against
everyday risks including dropping the protective eyewear onto the ground,
ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises
use for high speed particles at extreme temperatures.

CE European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be
sent on request.**

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical
solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the
complete product. If the frame is damaged also replace the complete product. After each
use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

PACKAGING AND EAN13 CODE			
	SPIPSI	SPIESP	SPIFLASH
Individual plastic bag	3660740003210	3660740003227	3660740003234
10 safety spectacles per inner box	3660740103217	3660740103224	3660740103231
300 safety spectacles per outer pack	3660740203214	3660740203221	3660740203238

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	Nylon + TPE
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY