

**1. PRODUCT AND COMPANY IDENTIFICATION**

Product Code	SKFXEBT
Product Name	Sikaflex EBT
Product Description	One component moisture curing polyurethane sealant.
Manufacturer/Supplier	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Isophorondiisocyanate	4098-71-9	0.10% - 1.00%	T, N	R23, R36/37/38, R42/43, R51/53

3. HAZARD IDENTIFICATION

Main Hazards Not classified as hazardous.

4. FIRST AID MEASURES

Eye Contact	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
Skin Contact	Wipe off as much as possible with a clean dry cloth. If material proves difficult to remove, use suitable skin cleanser (not solvent). Wash skin thoroughly with soap and water. Solvents should not be used to clean skin because they may increase the penetration of the material. Contaminated clothing should be washed or dry-cleaned before re-use.
Ingestion	Do not induce vomiting. Wash out mouth with water. Obtain medical attention.
Inhalation	Unlikely to occur. However provide symptomatic medical treatment if required.

5. FIRE FIGHTING MEASURES

Extinguishing Media	Use water spray, foam, dry chemical or carbon dioxide.
Special Hazards of Product	Combustion will release oxides of carbon and nitrogen with possible HCl
Protective Equipment for Fire-Fighting	Wear full protective clothing and self-contained breathing apparatus.



6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Remove spilled/leaked product by scraping from surfaces. Allow to solidify normally. Clean surfaces with a suitable solvent.

7. HANDLING AND STORAGE

<i>Handling</i>	Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices. Avoid contact with eyes, skin and clothing. Use in well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits - GB

Isophorondiisocyanate	UK EH40: WEL 0.02mg/m ³ 8h TWA. UK EH40: WEL 0.07mg/m ³ 15min STEL.
-----------------------	--

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required. Good ventilation is recommended during use
<i>Hand Protection</i>	Wear suitable impervious gloves. The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Wear safety glasses if risks of accidental contamination are possible during application.

9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste.
<i>Color</i>	Various
<i>Odor</i>	Characteristic.
<i>Flash Point °C</i>	Exceeds 65.
<i>Solubility - Water</i>	Insoluble.
<i>Density (kg/m³)</i>	Approx. 1200 at 20 °C.
<i>Viscosity (at 20°C)</i>	Thixotropic paste

10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Conditions to avoid</i>	Exposure to water or moisture.
<i>Hazardous Decomposition Products</i>	Combustion will generate: oxides of carbon. oxides of nitrogen. hydrogen chloride. toxic nitrogen compounds. acrid smoke and irritating fumes.



11. TOXICOLOGICAL INFORMATION

Acute toxicity Low order of acute toxicity.
Sensitization - Skin The possibility of allergic sensitisation should be considered.

12. ECOLOGICAL INFORMATION

Mobility Because of its high viscosity, low water solubility and low degree of toxicity, this material should not present any environmental problems.
Ecotoxicity The product is expected to be non-hazardous to aquatic species.

13. DISPOSAL

Product Disposal If possible allow the product to cure naturally in open air.
Disposal of bulk quantities and/or containers should be made through an authorised waste contractor.

14. TRANSPORT INFORMATION

ADR/RID : Proper shipping name Not Regulated under ADR/RID
IMDG : Proper shipping name Not Regulated under IMDG
IATA : Proper shipping name not Regulated under ICAO

15. REGULATORY INFORMATION

Risk Phrases None assigned.
Safety Phrases Contains isocyanates. See information supplied by the manufacturer.
Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
Aliphatic polyisocyanate
May produce an allergic reaction

16. OTHER INFORMATION

First Issue Date 18.08.2004
Revisions Highlighted Composition and Information on Ingredients
Uses and Restrictions Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
UK Legislation Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations
SI 2002/2677: The Control of Substances Hazardous to Health Regulations
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.



SAFETY DATA SHEET
Sikaflex EBT

Date of issue - 21/10/2005.

SKFXEBT

UK Guidance Publications

EH40, Occupational Exposure Limits, HSE. Revised Annually.
General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.