## 90° Template Profiler

Profilers with shank mounted bearing guides.

Ref. 46/91

Stage 1

to a template

BG

trend

Trimming

straight or

Ref. 46/300

shaped

- For use with router mounted above or below a table when following a template.
- For profiling and rebating applications only. Not for plunge cutting/grooving.
- A 3mm maximum overlap should be left before trimming.
- For replacement collars, see
   Spare Parts on pages 98 98.
- Refs. 46/910 and 46/91 have a shorter cutter length for use on thin boards. They are ideal for template making.

## 90° Double Guided Trimmer


- Ball bearings fitted to both nose and shank.
- Allows templates to be placed either on top or the bottom of the material, for ease of routing.
- Allows for irregular grained timber to be profiled more easily, by turning component other way up.

## 90° Template Oversize

- Oversize profiler allows component to be routed oversize to template.
- Useful when making jigs, templates and patterns.
- Can be used for trenching operations in shallow passes.

## 90° Trimmer & 'V' Groove

- Two flute.
- For trimming of laminate and solid lipping.
- 'V' groove to hide glue line.



Ref. 46/82

NEW SIZES

С

Ref. 46/80

	50	19.1	40	6/301	£52.50	£52.50
_	Replacement bearings					
8	For 46/300 & 46/301 - on nose			19	£3.00	
	- on shank		В	19C	£4.50	
	C mm	D mm	E mm	Order Ref.	TC Shank Diameter	
	19	8	2.35	26/2	£27.00	
	19	12.7	3.2	26/3	£29.50	
Ī	Replacement bearings					
	For 26/2 For 26/3			B127	£4.50	
				B19	£3.00	
	C mm	d mm	D mm	Order Ref.		k Diameter /4"
	25.4	12.7	16	46/85	£19	9.00
Ī	Spare bearing					

B127A

**B14A** 

Order Ref.

46/80

46/82

B127A

ANUT/46/82

£3 00

£7.50

TC Shank Diameter

£3.00

£1.00

1/2"

£43.00

1/4"

£20.50

**TC Shank Diameter** 

3/8"

£40.50

£4.50

£3.00

£4.50

£9.50

£9.50

TC Shank Diameter

1/2"

£48 00

12mm

£48 00

£10.50

1/2"

£40.00

£40.50

£44.00

£42.50

1/4"

£18.00

£21.50

£26.00


£32.00

£24.00

£25.00



- Self-guiding triple flute cutters.
- Extra fine trimming and longer life.
- For trimming of laminate or plywood overlay.
- Ref. 46/82 has twin bearings for stability by increasing the bearing surface and is an industrial profiling tool for longer runs of work.



For 46/85

Alternative bearing

To reduce 'V' groove

С

mm

25.4

38.1

depth to 1.0mm

D

mm

12.7

12.7

Replacement bearing

For 46/80 & 46/82

Replacement nut

For 46/82

trend

С

mm

4

9.5

19.1

25

25

25 4

25.4

25 4

32

45

50

D

mm

12.7

12.7

15.9

15.9

25

12 7

19.1

26

12.7

25.4

19.1

Replacement bearings

For 46/95, 46/91,

For 46/90 & 46/92

For 46/09 & 46/94

D

mm

19 1

46/96 & 46/910

For 46/10

For 46/100

For 46/101

С

mm

25.4

Ref. 26/3

Order

Ref.

46/910

46/91

46/92

46/90

46/100

46/95

46/94

46/10

46/96

46/101

46/09

B127

**B16** 

B26E

B19C

B25G

B254G

Order

Ref.

46/300

**NOW WITH** 

CARBIDE

Ref. 46/09

NAMIC"

Stage 2

Trimming

to make a

smooth

accurate

pass