ANGLEFIX® MITRE GUIDE

Halves the angle for mitre joints.

Use for mitre cutting of frames, skirting, architrave and beading as well as basic marking out. It will set internal and external angles and can be used with hand mitre saws and snip-off saws.

- Halves angles to achieve correct cutting angle before cutting mitres.
- Use for mitre cutting of frames, skirting (not tall skirting), architraves and beading as well as basic marking out.
- Sets internal and external angles.
- Can be used with hand mitre and snip-off saws.

ANGLEFIX® £15.50



Position the tool in the unknown angle and the metal flag automatically halves the angle.



Position the long part parallel to the workpiece and set the sawblade parallel to the metal flag.



The result is a perfect fit.



Automatically

halves the angle.

Can also be used for marking-out. Position the tool with the metal flag pointing downwards, parallel to the workpiece. Draw a line along the long part of the tool.





Biscuit jointing blades for use with all biscuit jointing machines.

- Six Tungsten Carbide Teeth.
- Anti-kickback tool design for safer use.
- Suitable for natural timbers, particle and MDF boards.
- Standard 100mm diameter x 22mm bore x 4mm kerf.

Craft Pro

CR/BJB100T **€19.00** Thin body for Trend, Freud & Casals

CR/BJB100 **€19.00**

Bossed body. Waveform

BJB/100S £36.50

Bossed body with scriber tooth.



BSC/MIX/100