

PRODUCT DATA

2600 / 2600AE.0.75 - Marking Aerosol

DESCRIPTION

RUST-OLEUM® Marking Aerosol is a quick drying quality paint for professional marking purposes at public works (utility works/telecom) building works and industrial sites and adheres to almost any substrate.

By means of the 360° valve the aerosol is sprayable in all directions.

RUST-OLEUM® Marking Aerosol 2600 is based on a fast drying acrylic resin. Except for 2692, which is based on a short oil alkyd.

RUST-OLEUM® Marking Aerosol 2600AE.0.75 is based on a short oil alkyd.

All products in this range are based on lead- and chromate free pigments.

RECOMMENDED USES

RUST-OLEUM® Marking Aerosol 2600 can be used on metal, concrete, asphalt, gravel, soil and grass, etc.

RUST-OLEUM® Marking Aerosol 2600 is not water-soluble and should be used in light industrial exposures, normal humidity and interior applications.

RUST-OLEUM® Marking Aerosol 2600 is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety.

TECHNICAL DATA

Appearance: Flat
Colour: See colour chart
Propellant: Dimethyl ether
VOC-content: 637 - 654 g/l

Drying times 20°C/50% r.h.
To touch: 20 minutes (500 ml version 60 seconds)
To recoat: Within 1 hour or after 48 hours
Full hardness: 7 days

Heat resistance: 100°C (dry heat)

Coverage

Theoretical: 500 ml: 1,5 m² per spray can at 25 µm dry (depending on colour)
750 ml: 2,25 m² per spray can at 25 µm dry (depending on colour)
Practical: Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Remove dirt, grease, oil and all other surface contaminants by appropriate means.
The surface must be clean and dry during application.

DIRECTION FOR USE

Remove cover cap. Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use.
It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

APPLICATION CONDITIONS

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu

PRODUCT DATA

2600 / 2600AE.0.75 - Marking Aerosol

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu